

RV Underbunk Air Conditioner 230V with Heat Pump

The compact design allows installation under the bed or inside the vehicle furniture without any roof modifications.

The unit combines cooling, heating, dehumidifying, and ventilation in one system.

Thanks to the heat pump and an additional 500 W heating element, it provides effective heating even at low outdoor temperatures.

Technical Data:

Power supply: 220–240 V AC / 50 Hz

Cooling capacity: 2800 W

Heating capacity: 2800 W (heat pump)

Additional heater: 500 W

Max. heating capacity: 3400 W

Power consumption – cooling: 400–990W

Power consumption – heating: 480–1100W

Starting current: 20 A (150 ms)

Airflow: up to 400 m³/h

Recommended room volume: up to 30m³

Refrigerant: CFC-free

Protection class: IPX5

Operating temperature range:

–15 °C to +43 °C

Weight: 28 kg

EER: 2.7

COP: 2.8

Fan speeds: 3 + AUTO

Dimensions:

754 × 398 × 276 mm (L × W × H)

Control:

Wireless remote control

Wall control panel (Wall Pad) with LCD display

Control functions: ope

Functions:

Cooling

Heating (heat pump + heater)

Dehumidifying

Ventilation

Auto mode

ON / OFF timer

Temperature adjustment range:
18–30 °C

